





**ON-THE-GO PRINTING
BEYOND THE COUNTER.**

Think big, with small. Epson's portable printer TM-P20 delivers mobility with efficiency in its compact size and rugged design, capable of fast print speeds of up to 100mm/s and a drop rating of 1.98m. Featuring a best-in-class operational battery life, fast Near Field Communication (NFC) pairing and a versatile compatibility with multiple smart devices, it is ideally suited for on-the-go printing – from retail to hospitality across various business applications. Reliable and easy to use, the TM-P20 is vital in elevating your business' productivity.



- 
Compact
- 
Mobility
- 
Print
- 
Cost Effective

ENGINEERED FOR BUSINESS

High Performance, Small Footprint

Discover a lightweight of 221g along with ultra-compact features and multiple connectivity options.

Industry-leading Battery Life

Ensure uninterrupted service to customers with up to 16 hours operational battery life for Wi-Fi models and 26 hours for Bluetooth models.

Easy Setting and Configuration

Comes complete with ESC/POS®, OPOS, JavaPOS and Windows® drivers which allow instant compatibility with existing POS solutions.



| | |
|---------------------------------------|--|
| MODEL NUMBER | TM-P20 |
| Print Technology | |
| Printing Method | Thermal line printing |
| Print Font | |
| Font | Font A: 12 x 24 32cpl; Font B: 9 x 24 42cpl (Default); Font C: 9 x 17 42cpl; Font D: 10 x 24 38cpl; Font E: 8 x 16 48cpl |
| Character Size (W x H) | Font A: 1.5 x 3.0mm; Font B: 1.12 x 3.0mm; Font C: 1.12 x 2.1mm; Font D: 1.25 x 3.0mm; Font E: 1.0 x 2.0mm |
| Character Set | 95 Alphanumeric, 18 International, 128 x 43 Graphic Bar code: UPC-A, UPC-E, JAN8/EAN8, JAN13/EAN13, ITF (Interleaved 2 of 5), Codabar (NW-7), Code 39, Code 93, Code 128, GS1-128 (UCC/EAN-128), GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, 2D symbol, PDF417, Datamatrix, QR Code, Maxi Code, Composite Aztec |
| Interface | 802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 3.0 (EDR supported) |
| Data Buffer | 4000 bytes |
| Print Speed Max. | 100 mm/sec (Receipt Version) |
| Dot / Line | 384 dots |
| Dot / Inch | 203 dpi |
| Paper | |
| Dimensions (mm) | Roll paper: 57.5 ± 0.5 (W) x Dia. 40.4 |
| Power | Custom Lithium-Ion Battery Pack, AC Adapter (Option) |
| Power Saving | Auto Power-off Function, Wi-Fi Power-saving Function |
| Charging | AC Adapter (3 hours to Full Charge) |
| Battery Life* | Wi-Fi: 9 hours Wi-Fi (Energy saving mode): 16 hours Bluetooth: 26 hours |
| Operating Temperature | 10 to 50° C (14 to 122° F) Bluetooth Model, 0 to 50° C (32 to 122° F) Wi-Fi Model |
| Humidity | 10 – 90% RH |
| Drop Rating | Test Rating of 6.5 feet |
| Reliability | |
| Printer Mechanism Life | 10 million lines |
| MTBF | 120,000 hours |
| MCBF | 16,000,000 lines |
| Colour | Epson Black (EBCK) |
| Overall Dimensions (W x D x H) | 79.0 x 119.8 x 43.6mm (Belt clip included) |
| Mass (Approx.) | Wi-Fi Model: Approximately 221 g (0.49 lb) Bluetooth Model: Approximately 212 g (0.47 lb) (Battery included; Belt Clip and Roll Paper Excluded, and Single Charger not included) |
| Options | Single Printer Charger/Cradle (OT-SC20), Battery Pack (OT-BY20), Padded Case (OT-PC20), Battery Spacer (OT-BS20) |
| Standard Accessories ROM | Roll Paper x 1 Roll (For Checking the Initial Movement of the Printer), CD-ROM (Drivers, Utility software, Manuals), Setup guide, Battery, Printer Charger, Belt Clip |
| General Information | |
| Supported Operating Systems | Mobile iOS, Android and Windows, (Security Level WEP, WPA, WPA2-Personal/Enterprise) |
| ROM | 64 MB |
| NV Area | User NV 1 KB, NV Graphics 384 KB |
| Audible Alert | Programmable Buzzer |
| Sensors | Paper End, Cover Open, BM Sensor |
| LED Indicators | Battery Charge Level, Power Status, Error Condition |
| Software | TM-P20 Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P20 Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page |
| Easy Setting | Easy Connection for Bluetooth – NFC, Easy Connection for Wi-Fi – NFC, Easy Connection for Bluetooth – Barcode, Easy Connection for Wi-Fi – Barcode, Easy Wi-Fi Setting – AdHOC Mode |

Dimensions & Weight

Weight: Approx. 221 g (0.49 lb)



Legend

dpi dots per 25.4 mm (dots per inch)
cpl characters per line

*P20 battery life can vary significantly depending on usage.

© 2015 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp

Information correct at time of printing
Printed August 2018